

# rialto wax 15



Protective emulsion for lime based interior surfaces

**rialto wax 15** is an emulsion blend of natural waxes to protect and polish interior walls, a specific product to treat smooth finishes as marmorino, venetian plasters and stuccos based on seasoned slaked lime. It is composed of natural waxes, soap, water-soluble solvents, siloxane additives, water.

## PROPERTIES

**rialto wax 15** stands out for the following characteristics:

- it is water based emulsion
- it has an agreeable smell
- it is ready to use
- it is easy to apply
- it is water repellent
- it doesn't influence the color tone of the lime finish
- it gives a translucent and smooth effect
- it can be tinted with inorganic rialto tinting pastes (max 0,2-0,5%)

**rialto wax 15** is made up of natural waxes, soap, water-thinnable solvents, siloxane additives, scent, water.

**rialto wax 15** is marked by the following properties:

- aspect: creamy liquid
- color: from white to light-brown
- odor: scent of honey
- specific weight: 0,91 kg/l
- water solubility: partially soluble in water

## PURPOSES

**rialto wax 15** is ideal to:

- protect interior surfaces decorated with lime based spatula stuccos, marmorino and Venetian plasters based on seasoned slaked lime
- confer to walls a high water repellency while keeping a good water vapor permeability
- give to walls a long lasting protection and clean appearance
- reduce risks of salt efflorescence and mould growth

## WORKING INSTRUCTION

- product ready to use, do not dilute
- shake well **rialto wax 15** before use
- apply by brush, woolen cloth or synthetic sponge
- use a dry woolen and clean cloth for the final polishing until complete absorption and dry
- proceed spreading the liquid product by portions of about 1 m<sup>2</sup> and polish before full absorption
- viscosity of the product may vary according to the room temperature. It is creamier at temperatures <25 °C (77 °F) and more fluid at temperatures > 26 °C (79 °F)
- temperature of the wall should be in between 10 °C (50 °F) and 30 °C (86 °F)
- store the product at a temperature below 30°C (86 °F) and above 5 °C (41°F)
- clean tools with water immediately after use
- do not discharge into the environment
- dispose of waste through authorized waste disposal

Maintenance instructions:

- treated walls can be easily cleaned using a dry woolen cloth
- if necessary it is possible the use of a sponge and natural liquid soap diluted in water. Squeeze well the sponge before use and clean the surface. Rinse and clean the sponge frequently during the process

## COVERING CAPACITY

The covering capacity is of 7m<sup>2</sup>/l (75 sq. ft/l) average but it can change depending on the nature and absorption of the substrate.

## PACKAGING

**rialto wax 15** is available in 1 l containers.

For further help or information regarding the products in the **rialto** range contact your local dealer.

Every care has been taken to ensure that the information provided in this technical data sheet is accurate. **rialto** is unable to guarantee results as it has no control over the conditions under which its products are applied.